

HEL Series

The DIRECTOR™

Hazardous Location Emergency LED



SPECIFICATIONS

Voltage	120VAC / 277VAC
Wattage	Stand-By - 8W (sign only) EM Mode - 16W (sign + 2X 4W 6V LED lamps)
Housing	Polycarbonate housing / aluminum backplate.
Color	Gray with red exit lettering.
Ambient Temp.	10°C (50°F) to 40°C (104°F)
T-Rating	T4A
Battery Type	6V nickel-cadmium battery
Battery Watts	20W
Battery Runtime	90 minutes
Warranty	5 Year Limited Warranty

Recommended Horizontal Spacing	
7' mounting height	39" center-to-center
15' mounting height	34" center-to-center

PRODUCT ORDERING SELECTION

The Director Part Number: **HEL10-010-40-U-X**

Remote head available - see RHE Series - The Extender™ PN: RHE-1-LA-GY



5935 West 84th St. | Indianapolis, IN 46278 | 1-888-391-4822 | www.SolasRay.com

Cat. #	Type
Notes	

CERTIFICATIONS / RATINGS



CLASS / DIVISION

- Class I, Div 2, Groups A, B, C, D

KEY FEATURES AND BENEFITS

- LED exit sign with two (2) emergency 4 watt LED lamp heads.
- 6V-20W nickel-cadmium battery for 90 minutes of emergency illumination.
- NEC, OSHA and NEMA compliant for above classes and groups.
- Meets NFPA101 (Life Safety Code), NFPA 70-NEC and OSHA illumination standards.
- Damp and wet location.
- NEMA 3, 4, 4X, and 12 rated.
- 10°C (50°F) to 40°C (104°F) ambient temperature capabilities.
- Includes advanced diagnostics (non-audible) / magnetic test switch.
- Fully gasketed housing frame.
- Heavy-duty vandal-resistant polycarbonate faceplate.
- Heavy-duty aluminum backplate.
- Vandal-resistant UV stabilized polycarbonate lamp cover.
- Stainless steel tamper-proof screws.
- 6 inch red exit lettering / field-selectable chevrons.
- Backplate features universal knockouts for a standard 4" junction box and 4 eyelets used in wall mount applications.
- 1/2" conduit entry on top and sides.

WEIGHT AND DIMENSIONS

