





Hazardous Location LED Fixtures with Internal EM Battery Quick Reference Guide


ROUND


The Sentinel 16" / 17.5" dia.		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJCR	14,000 lm ~ 39,200 lm	100W ~ 280W	C1D1 / C1D2 / C2D1 / C2D2 / C3	90 min	60°C / 140°F	IP66 / IP67

The Foreman 14.6" dia.		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJBR	16,200 lm ~ 28,000 lm	100W ~ 200W	C1D2 / C2D1 / C2D2 / C3	90 min	40°C / 104°F	IP66 / IP67


LINEAR


The Keeper 3 30" / 42.5" length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HTL3	18,200 lm ~ 23,800 lm	140W ~ 170W	C1D1	120 min	40°C / 104°F	IP67

The Steward 2' / 4' length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJIL	2,800 lm ~ 16,800 lm	20W ~ 120W	C1D1 / C1D2 / C2D1 / C2D2 / C3	90 min	60°C / 140°F	IP66


The Flyer 2' / 4' length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJHL	2,800 lm ~ 11,200 lm	20W ~ 80W	C1D2 / C2D1 / C2D2 / C3	90 min	60°C / 140°F	IP66


The Brute 2' / 4' length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HBRL	4,200 lm ~ 11,000 lm	40W ~ 105W	C1D1 / C2D1 / C2D2	90 min	40°C / 104°F	IP66


The Sting Ray 2' / 4' length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HCSR	4,020 lm ~ 9,530 lm	30W ~ 75W	C1D2	90 min	50°C / 122°F	IP66

The Rascal 27.5" / 51.25" length		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJRL	4,000 lm ~ 8,400 lm	30W ~ 60W	C1D2 / C2D1 / C3	90 min	50°C / 122°F	IP66 / IP67

FLOOD

The Patroller 12.6"x9.5" / 16.7"x11.8"		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJAS	11,200 lm ~ 56,000 lm	80W ~ 400W	C1D2 / C2D1 / C2D2 / C3	90 min	55°C / 131°F	IP66

The Dominator 11.6"x11.6" / 15.7"x11.2"		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HJDS	2,800 lm ~ 28,000 lm	20W ~ 200W	C1D1 / C1D2 / C2D1 / C2D2 / C3	90 min	55°C / 131°F	IP66

The Warden 8"x8" / 12"x12" / 16"x16"		Series	Min / Max Lumens	Watts	Class / Division	Battery Run-Time	Max Ambient Temp.	IP Rating
		HCS	5,000 lm ~ 23,125 lm	40W ~ 185W	C1D2	90 min	55°C / 131°F	IP67