

HIGH AMBIENT TEMPERATURE

AT-A-GLANCE

LED Lighting Quick Reference Guide

55°C to 115°C

All products featured in this document have a max. ambient temperature rating of 55°C (131°F) or higher.



ALWAYS THE RIGHT LIGHT

When you think of high ambient temperature lighting, think Solas Ray™. We have both the in-house expertise and variety of HazLoc products to make sure you get the right solution the first time.

★ Indicates products that have a maximum ambient temperature rating of 40°C (104°F) when used in hazardous locations. These products have a higher ambient temperature rating (shown in charts below) when used in non-hazardous locations.

Indicates Buy American Act (BAA) qualified.

Indicates Trade Agreement Act (TAA) qualified.

ROUND Industrial High Bay Lighting

The Goliath™



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HBGO-225	225w	5K	25,000 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (221°F)	---	IP66
HBGO-350	350w	5K	39,250 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (221°F)	---	IP66
HBGO-500	500w	5K	60,000 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (221°F)	---	IP66

20.5" dia. x 8.25" h / 24.44" dia. x 8.69" h


The Beast™ E2



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
DBL-210	210w	5K	20,706 lm	---	120 / 277 / 347 / 480	-70°C to +100°C (212°F)	---	IP66
DBL-350	350w	5K	35,000 lm	---	120 / 277 / 347 / 480	-70°C to +100°C (212°F)	---	IP66

20" dia. x 10.44" h

The Beast™



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
BL06-049	49w	4K / 5K	5,800 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL12-104	104w	4K / 5K	14,000 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL18-144	144w	4K / 5K	18,600 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL22-175	175w	4K / 5K	22,400 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL27-219	219w	4K / 5K	26,700 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL32-260	260w	4K / 5K	33,300 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL40-328	328w	4K / 5K	41,000 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66
BL50-384	384w	4K / 5K	48,600 lm	---	120-277 / 227-480 / 250DC	-40°C to +65°C (149°F)	---	IP66

20" dia. x 11" h

LINEAR Industrial High Bay Lighting

The PPD Series



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
PPD-20X1	20w	5K	2,500 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-35X1	35w	5K	4,375 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-20X2	40w	5K	5,000 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-20X3	60w	5K	7,500 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-35X2	70w	5K	8,750 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-20X4	80w	5K	10,000 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-35X3	105w	5K	13,125 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66
PPD-35X4	140w	5K	17,500 lm	---	120 / 277 / 347 / 480	-80°C to +105°C (239°F)	---	IP66

1,2,3 or 4 modules

HB6 Series

60" length

48" length

36" length

24" length



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HB6-2480W	80w	4K / 5K	11,200 lm	---	120-277	-30°C to +55°C (131°F)	---	IP66
HB6-36100W	100w	4K / 5K	14,000 lm	---	120-277	-30°C to +55°C (131°F)	---	IP66
HB6-48160W	160w	4K / 5K	22,400 lm	---	120-277 / 277-480	-30°C to +55°C (131°F)	---	IP66
HB6-60200W	200w	4K / 5K	28,000 lm	---	120-277 / 277-480	-30°C to +55°C (131°F)	---	IP66

The Maestro™




Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
LQMA-2-025	25w	4K / 5K	4,212 lm	---	120-277 / 347-480	-40°C to +55°C (122°F)	---	IP66
LQMA-2-035	35w	4K / 5K	5,559 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-2-050	50w	4K / 5K	8,356 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-4-050	50w	4K / 5K	8,356 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-4-075	75w	4K / 5K	12,719 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-4-100	100w	4K / 5K	16,695 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-8-150	150w	4K / 5K	23,497 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66
LQMA-8-200	200w	4K / 5K	30,757 lm	---	120-277 / 347-480	40°C to +55°C (122°F)	---	IP66

24" / 48" / 96" length

Specifications and data are subject to change without notice.

ROUND HazLoc LED Lighting


The HazLoc Beast™



20" dia. x 9" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HH06-49	49w	4K / 5K	5,772 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH12-104	104w	4K / 5K	13,342 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH18-144	144w	4K / 5K	18,018 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH22-175	175w	4K / 5K	21,157 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH27-219	219w	4K / 5K	25,558 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH32-260	260w	4K / 5K	32,640 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66
HH40-328	328w	4K / 5K	40,945 lm	C1D2, C2D2	120-277 / 277-480	-40°C to +65°C (149°F)	T5	IP66

The Sentinel™



16" dia. x 13.4" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJCR1L-040	40w	4K / 5K	5,600 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-060	60w	4K / 5K	8,400 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-080	80w	4K / 5K	11,200 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-100	100w	4K / 5K	14,000 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-150	150w	4K / 5K	21,000 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-200	200w	4K / 5K	28,000 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-250	250w	4K / 5K	35,000 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67
HJCR1L-280	280w	4K / 5K	39,200 lm	C1D1&2, C2D1&2	120-277 / 347-480	-40°C to +60°C (140°F)	T4	IP66 / IP67

The Monitor™ (C)



9.21" dia. x 7.61" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTR91C-060	60w	3K / 5K	6,000 lm	C1D1, C2D1	120 / 277 / 480	-40°C to +100°C (212°F)*†	T4	IP67
HTR91C-080	80w	3K / 5K	8,000 lm	C1D1, C2D1	120 / 277 / 480	-40°C to +85°C (185°F)*‡	T4	IP67
HTR91C-100	100w	3K / 5K	10,000 lm	C1D1, C2D1	120 / 277 / 480	-40°C to +65°C (149°F)*	T4	IP67
HTR92C-060	60w	3K / 5K	6,000 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +100°C (212°F)*†	T4	IP67
HTR92C-080	80w	3K / 5K	8,000 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +85°C (185°F)*‡	T4	IP67
HTR92C-100	100w	3K / 5K	10,000 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +65°C (149°F)*	T4	IP67

† 60w 480v models have a maximum ambient temperature rating of +85°C (185°F)

‡ 80w 480v models have a maximum ambient temperature rating of +65°C (149°F)


The Guard™ (C)



10.95" dia. x 9.6" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTR11C2-120	120w	3K / 5K	12,000 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +85°C (185°F)*	T3C, T6	IP67
HTR11C2-140	140w	3K / 5K	14,000 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +65°C (149°F)*	T3C, T6	IP67

The Lookout™ (C)



7.25" dia. x 6.21" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTR7C1-040	40w	3K / 5K	4,000 lm	C1D1, C2D1	24 / 120 / 277 / 480	-40°C to +100°C (212°F)*†‡	T6, T4	IP67
HTR7C1-060	60w	3K / 5K	6,000 lm	C1D1, C2D1	24 / 120 / 277 / 480	-40°C to +85°C (185°F)* ‡	T6, T4	IP67
HTR7C2-040	40w	3K / 5K	4,000 lm	C1D2, C2D1	24 / 120 / 277 / 480	-40°C to +100°C (212°F)*†‡	T4, T3C	IP67
HTR7C2-060	60w	3K / 5K	6,000 lm	C1D2, C2D1	24 / 120 / 277 / 480	-40°C to +85°C (185°F)* ‡	T4, T3C	IP67

† 40w 480v models have a maximum ambient temperature rating of +85°C (185°F) ‡ 24v models have a maximum ambient temperature rating of +65°C (149°F)



The Pilot™



6.8" dia. x 16.1" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJGJJ1-010	10w	4K / 5K	1,000 lm	C1D1&2, C2D1&2	100-277	-40°C to +65°C (149°F)	---	IP66
HJGJJ1-020	20w	4K / 5K	2,000 lm	C1D1&2, C2D1&2	100-277	-40°C to +65°C (149°F)	---	IP66
HJGJJ1-030	30w	4K / 5K	3,000 lm	C1D1&2, C2D1&2	100-277	-40°C to +65°C (149°F)	---	IP66
HJGJJ1-040	40w	4K / 5K	4,000 lm	C1D1&2, C2D1&2	100-277	-40°C to +65°C (149°F)	---	IP66

The Spotter™




4.84" dia. x 7.6" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTR5-020	20w	3K / 5K	2,000 lm	C1D2, C2D2	24 / 120 / 277 / 480	-65°C to +85°C (185°F)*†	T3B, T5	IP67

† 24v models have a maximum ambient temperature rating of +65°C (149°F)

FLOOD HazLoc LED Lighting

Mini Max™



8.5" x 10" x 5"

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HGMM1-020	20w	3K/4K/5K	3,200 lm	C1D1	120-277 / 347-480	-40°C to +65°C (149°F)	T6	IP66/IP67
HGMM1-040	40w	3K/4K/5K	6,400 lm	C1D1	120-277 / 347-480	-40°C to +65°C (149°F)	T6	IP66/IP67
HGMM1-060	60w	3K/4K/5K	9,600 lm	C1D1	120-277 / 347-480	-40°C to +65°C (149°F)	T6	IP66/IP67
HGMM2-020	20w	3K/4K/5K	3,200 lm	C1D2, C2D1&2	120-277 / 347-480	-40°C to +65°C (149°F)	T4A	IP66/IP67
HGMM2-040	40w	3K/4K/5K	6,400 lm	C1D2, C2D1&2	120-277 / 347-480	-40°C to +65°C (149°F)	T4A	IP66/IP67
HGMM2-060	60w	3K/4K/5K	9,600 lm	C1D2, C2D1&2	120-277 / 347-480	-40°C to +65°C (149°F)	T4A	IP66/IP67

The Sentry™



10.38" x 16.31" - 100w/150w

12.31" x 21.38" - 200w

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJSE-100	100w	3K/4K/5K	13,000 lm	C1D2, C2D1&2	120-277 / 480	-40°C to +60°C (140°F)	T4	IP66/IP67
HJSE-150	150w	3K/4K/5K	19,500 lm	C1D2, C2D1&2	120-277 / 480	-40°C to +60°C (140°F)	T4	IP66/IP67
HJSE-200	200w	3K/4K/5K	26,000 lm	C1D2, C2D1&2	120-277 / 480	-40°C to +60°C (140°F)	T3	IP66/IP67

Specifications and data are subject to change without notice.

FLOOD HazLoc LED Lighting (continued)

The Warden™



8" w x 8" d x 5.7" h - 40w
 12" w x 12" d x 6.4" h - 60w-100w
 16" w x 16" d x 6.6" h - 120w-185w
 32" w x 16" d x 6.6" h - 200w-370w

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HCS8-040	40w	3K/4K/5K	5,000 lm	C1D2	100-277	-40°C to +55°C (131°F)	T6	IP67
HCS12-060	60w	3K/4K/5K	7,500 lm	C1D2	100-277 / 200-480	-40°C to +55°C (131°F)	T6	IP67
HCS12-080	80w	3K/4K/5K	10,000 lm	C1D2	100-277 / 200-480	-40°C to +55°C (131°F)	T6	IP67
HCS12-100	100w	3K/4K/5K	12,500 lm	C1D2	100-277 / 200-480	-40°C to +55°C (131°F)	T6	IP67
HCS16-120	120w	3K/4K/5K	15,000 lm	C1D2	100-277 / 200-480	-40°C to +55°C (131°F)	T5	IP67
HCS16-150	150w	3K/4K/5K	18,750lm	C1D2	100-277 / 200-480	-40°C to +55°C (131°F)	T5	IP67
HCS16-185	185w	3K/4K/5K	23,125 lm	C1D2	100-277	-40°C to +55°C (131°F)	T5	IP67
HCS16-200	200w	3K/4K/5K	25,000 lm	C1D2	100-277	-40°C to +55°C (131°F)	T5	IP67
HCS32-240	240w	3K/4K/5K	30,000 lm	C1D2	100-277	-40°C to +55°C (131°F)	T5	IP67
HCS32-300	300w	3K/4K/5K	37,500 lm	C1D2	100-277	-40°C to +55°C (131°F)	T5	IP67
HCS32-370	370w	3K/4K/5K	46,250 lm	C1D2	100-277	-40°C to +55°C (131°F)	T5	IP67


The Dominator™



15.7" w x 11.3" h / 11.6" w x 11.6" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJDS1-020	20w	4K / 5K	2,800 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-040	40w	4K / 5K	5,600 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-060	60w	4K / 5K	8,400 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-080	80w	4K / 5K	11,200 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-100	100w	4K / 5K	14,000 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-150	150w	4K / 5K	21,000 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66
HJDS1-200	200w	4K / 5K	28,000 lm	C1D1&2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	---	IP66

The Attendant™



10.45" w x 5.12" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTRT-040	40w	3K / 5K	4,000 lm	C1D2	120 / 277 / 480	-40°C to +85°C (185°F)*	T4	IP67


The Navigator™



25.6" l x 11" w x 3.2" h

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HCCH-080	80w	3K/4K/6K	9,200 lm	C1D2	100-277 / 480	-40°C to +55°C (131°F)*	---	IP67

The Patroller™




9.84" w x 6.3" d x 6.54" h - 20w-60w
 12.6" w x 9.45" d x 6.29" h - 80w-100w
 16.65" w x 11.81" d x 8.27" h - 150w-400w

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJAS2-020	20w	4K / 5K	2,800 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-040	40w	4K / 5K	5,600 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-060	60w	4K / 5K	8,400 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-080	80w	4K / 5K	11,200 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-100	100w	4K / 5K	14,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-150	150w	4K / 5K	21,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-180	180w	4K / 5K	25,200 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-200	200w	4K / 5K	28,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-250	250w	4K / 5K	35,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-300	300w	4K / 5K	42,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66
HJAS2-400	400w	4K / 5K	56,000 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +55°C (131°F)	T3	IP66

Linear HazLoc LED Lighting


The Steward™



23.3" l x 5.5" w x 6.4" h - HJIL21
 46.1" l x 5.5" w x 6.4" h - HJIL41

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJIL21-020	20w	4K / 5K	2,800 lm	C1D1&2, C2D1&2	100-277 / 200-480	-40°C to +60°C (140°F)	T4	IP66
HJIL21-040	40w	4K / 5K	5,600 lm	C1D1&2, C2D1&2	100-277 / 200-480	-40°C to +60°C (140°F)	T4	IP66
HJIL21-060	60w	4K / 5K	8,400 lm	C1D1&2, C2D1&2	100-277 / 200-480	-40°C to +60°C (140°F)	T4	IP66
Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJIL41-060	60w	4K / 5K	8,400 lm	C1D1&2, C2D1&2	100-277 / 200-480	-40°C to +60°C (140°F)	T4	IP66
HJIL41-080	80w	4K / 5K	12,000 lm	C1D1&2, C2D1&2	100-277 / 200-480	-40°C to +60°C (140°F)	T4	IP66

The Flyer™




23.6" l x 4.7" w x 4.8" h - HJIL21
 47.1" l x 4.7" w x 4.8" h - HJIL41

Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJHL22-020	20w	4K / 5K	2,800 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +60°C (140°F)	T3	IP66
HJHL22-040	40w	4K / 5K	5,600 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +60°C (140°F)	T3	IP66
Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJHL42-040	40w	4K / 5K	5,600 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +60°C (140°F)	T3	IP66
HJHL42-060	60w	4K / 5K	8,400 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +60°C (140°F)	T3	IP66
HJHL42-080	80w	4K / 5K	11,200 lm	C1D2, C2D1&2	120-277 / 200-480	-40°C to +60°C (140°F)	T3	IP66

Specifications and data are subject to change without notice.

Linear HazLoc LED Lighting (continued)

The Keeper™ 2



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HTL22-040	40w	3K / 5K	4,833 lm	C1D2, C2D2	120 / 277	-40°C to +100°C (212°F)*	T4 / T4A†	IP67
HTL22-060	60w	3K / 5K	6,688 lm	C1D2, C2D2	120 / 277	-40°C to +85°C (185°F)*	T4 / T4A†	IP67
HTL22-120	120w	3K / 6K	12,000 lm	C1D2	120 / 277	-40°C to +65°C (149°F)*	T3C	IP67
HTL22-150	150w	3K / 6K	15,000 lm	C1D2	120 / 277	-40°C to +65°C (149°F)*	T3C	IP67

23.2"l x 6.9"w x 3.5"h - HTL22
46.4"l x 6.9"w x 3.9"h - HTL24



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HTL24-040	40w	3K / 5K	4,833 lm	C1D2, C2D2	120 / 277	-40°C to +100°C (212°F)*	T4 / T4A†	IP67
HTL24-080	80w	3K / 5K	9,414 lm	C1D2, C2D2	120 / 277 / 480	-40°C to +85°C (185°F)*	T4 / T4A†	IP67
HTL24-120	120w	3K / 5K	14,180 lm	C1D2, C2D2	120 / 277	-40°C to +65°C (149°F)*	T4 / T4A†	IP67
HTL24-240	240w	3K / 6K	24,000 lm	C1D2	120 / 277	-40°C to +65°C (149°F)*	T3C	IP67
HTL24-300	300w	3K / 6K	30,000 lm†	C1D2	120 / 277	-40°C to +65°C (149°F)*	T3C	IP67

† C1D2 T-rating is T4 / C2D2 T-rating is T4A

The Keeper™



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature*	T-Rating	IP Rating
HTL1-040	40w	3K / 5K	4,000 lm	C1D1, C2D2	120 / 277	-40°C to +100°C (212°F)*	T6	IP67
HTL1-060	60w	3K / 5K	6,000 lm	C1D1	120 / 277	-40°C to +85°C (185°F)* †	T6	IP67

25.85"l x 4.13"w x 6.46"h

† 60w 277v models have a maximum ambient temperature rating of +65°C (149°F)

Emergency HazLoc LED Lighting

The Guide™



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJJES-003	3w	---	---	C1D1&2, C2D1&2	100-277	-10°C to +60°C (140°F)	---	IP66
HJJES-005	5w	---	---	C1D1&2, C2D1&2	100-277	-10°C to +60°C (140°F)	---	IP66

15.59"w x 18.5"h x 4.5"d

The Commander™



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
CTL	6.5 - 11w	---	---	C1D1, C2D1	120 / 277	10°C to +45°C (131°F)	T6	IP65
CTLES (Exit)	6.5 - 11w	---	---	C1D1, C2D1	120 / 277	10°C to +45°C (131°F) †	T6	IP65

† 35°C (95°F) max ambient temperature when configured with a green exit sign.

19.75"w x 23.88"h x 5.63"d

HJVX Series



Model #	Wattage	Kelvin	Lumens	Class/Division	Voltage	Ambient Temperature	T-Rating	IP Rating
HJVX-05	5w	---	---	C1D2, C2D1&2	100-277	-20°C to +60°C (140°F)	---	IP66

16.125"w x 11.06"h
x 1.81"d

Specifications and data are subject to change without notice.