

HJGJJ Series

The PILOT™

Hazardous Location LED Lighting



High Vibration
RESISTANCE



5935 West 84th St. | Indianapolis, IN 46278 | 1-888-391-4822 | www.SolasRay.com

Cat. #	Type
Notes	

CERTIFICATIONS / RATINGS



CLASS / DIVISION

- Class I, Div 1, Groups C, D
- Class I, Div 2, Groups A, B, C, D
- Class II, Div 1, Groups E, F, G
- Class II, Div 2, Groups F, G
- Class III

KEY FEATURES AND BENEFITS

- Ambient temperature capabilities: -40°C (-40°F) to 65°C (149°F)
- Corrosion proof - coated aluminum alloy (copper free) housing.
- Marine rated protective powder coat.
- *DLC V5.1 Standard (20W/30W/40W models in 4000K/5000K)
- Wire guard included standard.
- Stainless steel hardware and bracket.
- Heavy duty and high impact resistance - IK10 rated.

SPECIFICATIONS

Voltage	100-277 VAC
Wattage	10W / 20W / 30W / 40W
Color Temp	4000 / 5000 Kelvin
Housing	Coated copper free aluminum alloy
Color	Gray
Lens	Tempered glass globe
Ambient Temperature	-40°C (-40°F) to 65°C (149°F)
Lifetime	100,000+ hrs L70

CRI	80
Beam Angle	120°
Entrance Thread	3/4" NPT
Protection	IP66
Warranty	5 Year Limited Warranty

LUMENS

10W	20W	30W	40W
1,400	2,800	4,200	5,600










PRODUCT ORDERING SELECTION

HJGJJ1	<input type="checkbox"/>	<input type="checkbox"/>	U	GL-HJGU	<input type="checkbox"/>
Series	Watts	Kelvin	Voltage	Lens	Mounting Options
<input checked="" type="checkbox"/> HJGJJ1	<input type="checkbox"/> 010 - 10W <input type="checkbox"/> 020 - 20W <input type="checkbox"/> 030 - 30W <input type="checkbox"/> 040 - 40W	<input type="checkbox"/> 40 - 4000K <input type="checkbox"/> 50 - 5000K	<input checked="" type="checkbox"/> U - 100-277 VAC	<input checked="" type="checkbox"/> GL-HJGU - Globe Lens with Wire Guard	<input type="checkbox"/> HJCB - Ceiling Bracket <input type="checkbox"/> HJCJB - Ceiling Junction Box <input type="checkbox"/> HJPP - Pendant Pipe <input type="checkbox"/> HJPP12 - 12° Pendant Pipe <input type="checkbox"/> HJEBPP - External Box with Pendant Pipe <input type="checkbox"/> HJPS25 - 25° Pole Stanchion <input type="checkbox"/> HJPS90 - 90° Pole Stanchion <input type="checkbox"/> HJW25 - 25° Junction Box Wall Arm <input type="checkbox"/> HJW90 - 90° Junction Box Wall Arm

HJGJJ Series

The PILOT™

MOUNTING OPTIONS

#HJCB - Ceiling Bracket	#HJCJB - Ceiling Junction Box	#HJPP - Pendant Pipe	#HJPP12 - 12° Pendant	
				
#HJEBPP - Ext. Box Pendant	#HJPS25 - 25° Pole Stanchion	#HJPS90 - 90° Pole Stanchion	#HJW25 - 25° Box Wall Arm	#HJW90 - 90° Box Wall Arm
	 <p>Fits 1.9" OD Pipe/Poles (Mount is 2 5/32" / 55mm ID)</p>	 <p>Fits 1.9" OD Pipe/Poles (Mount is 2 5/32" / 55mm ID)</p>		

WEIGHTS AND DIMENSIONS

WEIGHT

11.82 lb

