

SVW Series

The WIDE VAPOR TIGHT Industrial LED Lighting



5935 West 84th St. | Indianapolis, IN 46278 | 1-888-391-4822 | www.SolasRay.com

Cat. #	Type
Notes	

4ft model shown with
smooth frosted lens



2ft model shown with
smooth frosted lens



*64 configurations are DLC 5.1 qualified.
Consult factory for more information.



CERTIFICATIONS / RATINGS



IP65 IP66 IP67



NEMA
4X



UL-F1

KEY FEATURES AND BENEFITS

- Weatherproof wide area lighting for wet location and wash-down applications.
- Stainless steel cam latches are included standard.
- UL 5VA fiberglass enclosure (will not melt or burn).
- UL approved for through wiring.
- Poured in place gasket and cam latches seal the fixture.
- Occupancy sensor and emergency battery options available.
- Acrylic lens option is impact modified and recommended in areas with UV exp.
- Polycarbonate lens option is best in extreme temperature and high abuse areas.
- Lenses available in ribbed or smooth, frosted or clear.
- 0-10 V dimmable.
- 2ft and 4ft lengths available.
- UL F1 rated (suitable for outdoor use/exposure to ultraviolet light).
- Buy American Act compliant. BABA compliant.

SPECIFICATIONS

Voltage	120-277 / 347-480 VAC
Wattage	72W / 108W / 144W / 148W / 185W / 222W / 258W / 293W
Color Temp	3000 / 3500 / 4000 / 5000 Kelvin
Housing	UL 5VA Fiberglass

Color	White
Lens	Acrylic / Polycarbonate
Ambient Temperature	-30°C (-22°F) to 45°C (113°F)
Lifetime	>50,000 hrs L70
CRI	>80

Power Factor	>0.90
Protection	IP65 / IP66 / IP67
Entrance	1/2" diameter hole
Warranty	5 Year Limited Warranty

LUMENS (SVW2)

72W	108W	144W
~10,000	~15,000	~20,000

LUMENS (SVW4)

148W	185W	222W	258W	293W
~20,000	~25,000	~30,000	~35,000	~40,000

PRODUCT ORDERING SELECTION

Length	Watts	Voltage (VAC)	Lens Material	Lens Type	Kelvin	Mounting Options	Hub Location	Other Options*
<input type="checkbox"/> SVW2 (2 ft)	<input type="checkbox"/> 72 - 72W <input type="checkbox"/> 108 - 37W <input type="checkbox"/> 144 - 144W	<input type="checkbox"/> U - 120-277 <input type="checkbox"/> 48 - 347-480	<input type="checkbox"/> A - Acrylic (Std.) <input type="checkbox"/> P - Poly	<input type="checkbox"/> SF - Smooth Frosted (Standard) <input type="checkbox"/> SC - Smooth Clear	<input type="checkbox"/> 30 - 3000K <input type="checkbox"/> 35 - 3500K <input type="checkbox"/> 40 - 4000K <input type="checkbox"/> 50 - 5000K	<input type="checkbox"/> CMBW - Ceiling Mount Brackets (2) <input type="checkbox"/> VHMW - V-Hook Hanging Mounts (2) <input type="checkbox"/> SPM - Single Pendant Mount <input type="checkbox"/> DPM - Double Pendant Mount*	<input type="checkbox"/> 2E - 2 Ends (Standard) <input type="checkbox"/> 1E - 1 End <input type="checkbox"/> 1T - 1 Top	<input type="checkbox"/> OS - PIR Occupancy Sensor (External) <input type="checkbox"/> OSM - Microwave Occupancy Sensor (Under The Lens) <input type="checkbox"/> EM10 - 10W Emergency Battery Backup <input type="checkbox"/> TPS - Tamper Proof Screws
<input type="checkbox"/> SVW4 (4 ft)	<input type="checkbox"/> 148 - 148W <input type="checkbox"/> 185 - 185W <input type="checkbox"/> 222 - 222W <input type="checkbox"/> 258 - 258W <input type="checkbox"/> 293 - 293W							

* Not available in 2ft length.

Note: Mounting options detailed on next page.

*Whip and Cordsets are available, see chart on next page. Add to end of part number.




SVW Series

The WIDE VAPOR TIGHT



5935 West 84th St. | Indianapolis, IN 46278 | 1-888-391-4822 | www.SolasRay.com

MOUNTING OPTIONS

#CMBW - Ceiling Mount Bracket	#VHMW - V-Hook Hanging Mounts	#SPM / DPM Pendant Mounts
 <p>Standard stainless steel ceiling mount. Allows 1.25" space for heat dissipation and air flow.</p>	 <p>Stainless V-Hook (bail) mount. Recommended for cable hanging.</p>	<p>Single and double pendant mounting available.</p> <p>Note: 2ft fixtures not available with double pendant mount.</p>  <p>Pendant By Others</p>

CUSTOM WHIP AND CORDSET ORDERING

Custom whips and cordsets can be added to vapor tight fixtures. Use the chart below to choose specifications and add to the end of the part number.



Type	# of Wires	Length	End Fitting	Color	Voltage	Amps (TL Only)
WP - Whip	3 - 3 Wire	(blank) - 6 feet	(blank) - No Plug	BK - Black	(blank) - 120-277V	15 - 15 Amps
CS - Cordset	4 - 4 Wire	8 - 8 feet	P - Standard Plug	WH - White	120 - 120V	20 - 20 Amps
	5 - 5 Wire	10 - 10 feet	TL - Twist-Lock		277 - 277V	
	6 - 6 Wire	12 - 12 feet			347 - 347V	
		15 - 15 feet			480 - 480V	

Example: to add a 3-wire, 6ft, white 120-277V cordset with a standard plug to a SV4-35-DMV-A-RF-30-CMB, the part number would be:

SV4-54-U-A-RF-30-CMBN-**CS3PWH**

DIMENSIONS

SVW2 - 2' Models



SVW4 - 4' Models

